



UV-STOP PC
 UV-STOP PC
 UV-STOP PC



UV-STOP PC	UV-STOP PC	UV-STOP PC	UV-STOP PC	UV-STOP PC	UV-STOP PC	UV-STOP PC
I	220V. 50 / 60Hz.	IP65.		-35 °C/+45 °C.	E27.	35



YMLED-6605



APPLICATION: DESCRIPTION



- Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
- Diffuser is made by high quality UV-stop PC lens.
- Heat resisting silicone rubber gasket.
- Protection grade: IP54
- Corrosion-proof capability: II
- Working condition: -35°C to +45°C
- Isolation class: 1
- Power voltage: 220V(±10%) 50Hz
- LED holder: E27/G12
- Max power: 70W



□□

1. FedEx / DHL / UPS / TNT □□ □□□□□□

2. □□□□□□ □□ □□□□fcl; □□/□□□□□□

3. □□□□□□□□□□□□□□□□□□

4. □□□□□ 5.□□ - 7□; 15. - 30. □□□□□□

□□□□

1. □□□ T / T. □□□□□ Moneygram. □ PayPal.; 30□□□□; 70□□□□ □□□□

2. MOQ □ 1□□

3. □□□ 5□