□□□□□□□□□□ □ □□

□□□□□□□□□□□□□□□
UV-STOP PC□□
□□□□□

□□□□□□□□□□□ □□

□□□□	□□	□□□□	□□□□	□□□□	□□□□	□□□□
I□	220V. 50 / 60Hz.	IP65.	□□	-35 °C□+45 °C.	E27.	35□

□□□□

APPLICATION: DESCRIPTION

- Lamp housing is made by die cast aluminum,surface treatment for electrostatic powder coating.
- Diffuser is made by high quality UV-stop PC lens.
- Heat resisting silicone rubber gasket.
- Protection grade:IP54
- Corrosion-proof capability:II
- Working condition:-35℃to+45℃
- Isolation class:1
- Power voltage:220V(±10%) 50Hz
- LED holder:E27/G12
- Max power:70W

□□□□□□□□□□□□

□□
1□ **FedEx / DHL / UPS / TNT** □□ □□□□□□□
2□ □□□□□□ □□ □□□□fcl;□□/□□□□□
3.□□□□□□□□□□□□□□□□□□□
4. □□□□□ 5.□□ - 7□; 15. - 30. □□□□□□
□□□□
1.□□□ **T / T.**□ □□□□□ **Moneygram.**□**PayPal.**; **30**□□□□; **70**□□□□ □□□□
2□ MOQ□ **1**□□
3.□□□5□