

What is the details of our LED Garden light?

Die cast aluminum housing,surface treatment for electrostaic power coating
UV-stop PC lamp cover
Sealed lamp housing

What is the Specifications of our LED Garden light?

Insulation class	Power supply	LED current	Power Factor	Working Ambient	Life span	CRI	CCT
Class I	120-277V 50/60HZ	700mA	>0.95	-35 °C to +45 °C	>30,000hrs	RA>75	3000K-6500K


Product Code	YMLED-6307
LED Qty	13pcs
Rated Power	30w
Luminous Flux	2000lm
G.W/N.W	15/13kgs
Packing Size	250x250x1830mm

Product Photos

YMLED-6307



YMLED-6307



Product description:

- Aluminum die-casting housing.
- Photogy PMMA Diffuser.
- Anti-glare aluminum oxide reflector.
- High power LED with anti-glare diffuser plate.

Product description:

- Protection grade:IP65
- Corrosion-proof capability:II
- Working condition:-35°C~ +45°C
- Isolation class:1
- Power voltage:170-220V 50-60Hz
- High:2.8m
- Max power:30W

Packaging & Shipping ,Trade Terms:

Shipping

1. **FedEx/DHL/UPS/TNT** for **samples**, Door-to-Door,
2. **By Air or by Sea** for **batch goods**, for FCL; Airport/ Port receiving,
3. Customers specifying freight forwarders or negotiable shipping methods,
4. **Delivery Time**: 5-7 days for samples; 15-30 days for batch goods.

Payment Terms

1. Payment: **T/T, Western Union, MoneyGram, PayPal; 30% deposits; 70% balance** before delivery,
2. MOQ: **1pcs**,
3. Warranty: 5years