

□□□□□□□□□□□□□□□□? □□□~□□□□

□□ □□□ □□□□ □□□□, □□□□ □□□□ □□ □□
UV-Stop PC □□ □□
□□ □ □□ □□□□

□□□□□□□□□□□□□□? □□□

□□ □□	□□ □□ □□	□□ □□	□□ □□ □□	□□□□□ □□	□□ □□	□□ □□
□□□ I.	220V. 50 / 60hz.	IP65.	□□□ II.	-35. ° C ~ +45. ° C.	E27.	35W.

□□ □□□

YMLLED-6607



APPLICATION: DESCRIPTION



- Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
- Diffuser is made by high quality UV-stop PC lens.
- Heat resisting silicone rubber gasket.
- Protection grade: IP54
- Corrosion-proof capability: II
- Working condition: -35°C to +45°C
- Isolation class: I
- Power voltage: 220V(±10%) 50Hz
- LED holder: E27/G12
- Max power: 70W

TERMS AND CONDITIONS :

□□

1. FedEx / DHL / UPS / TNT. ~□□□ □□, □□ - □,
2. □□ □□ □□□ ~□□□□ □□ □□, fcl; □□ / □□ □□,
3. □□ □□ □□ □□ □□ □□ □□ □□□□ □□,
4. □□ □□: 5.□□□□□□ -7 □; 15.-30. □□ □□□ □.

□□ □□

1. □□ : T / T., □□□ □□□, □ □□,□□□...□ 30 % □□...□ 70 % □□ □□ □□,
2. MOQ : 1pcs,
3. □□ : 5years.