What is the details of our **LED Bollard light**?

Die cast aluminum housing,surface treatment for electrostaic power coating UV-stop PC lamp cover Sealed lamp housing

What is the Specifications of our LED Bollard light?

Insulation class	Power supply	LED current	Power Factor	Working Ambient	Life span	CRI	CCT
Class I	120-277V 50/60HZ	700mA	>0.95	-35 °C to +45 °C	>30,000hrs	RA>75	3000K-6500K

Product Code

LED Qty

Rated Power

Luminous Flux

G.W/N.W

Packing Size

YMLED-6221 4pcs 8w 500-600lm 5/4.5kgs 250x250x830mm

Product Photos

YMLED-6222

PRODUCT DETAILS



Packaging & Shipping ,Trade Terms:

- Shipping
 1. FedEx/DHL/UPS/TNT for samples, Door-to-Door,
 2. By Air or by Sea for batch goods, for FCL; Airport/ Port receiving,
 3. Customers specifying freight forwarders or negotiable shipping methods,

Delivery Time: 5-7 days for samples; 15-30 days for batch goods.
 Payment Terms
 Payment: T/T, Western Union, MoneyGram,PayPal; 30% deposits; 70% balance before delivery,
 MOQ: 1pcs,
 Warranty: 5years