

## What is the details of our [wall light](#)?

Die cast aluminum housing,surface treatment for electrostaic power coating

UV-stop PC lamp cover

Sealed lamp housing

## What is the Specifications of our wall light?

Insulation class	Power supply	Protection grade	Corrersion-proof capability	Working Ambient	Lamp holder	Max power
Class I	220V 50/60HZ	IP65	Class II	-35 °C to +45 °C	E27	35W

## Product Photos

# YMLED-6605



## APPLICATION: DESCRIPTION



- Lamp housing is made by die cast aluminum, surface treatment for electrostatic powder coating.
- Diffuser is made by high quality UV-stop PC lens.
- Heat resisting silicone rubber gasket.
- Protection grade: IP54
- Corrosion-proof capability: II
- Working condition: -35°C to +45°C
- Isolation class: I
- Power voltage: 220V(±10%) 50Hz
- LED holder: E27/G12
- Max power: 70W

## Packaging & Shipping , Trade Terms:

### Shipping

1. **FedEx/DHL/UPS/TNT** for **samples**, Door-to-Door,
2. **By Air or by Sea** for **batch goods**, for FCL; Airport/ Port receiving,
3. Customers specifying freight forwarders or negotiable shipping methods,
4. **Delivery Time:** 5-7 days for samples; 15-30 days for batch goods.

### Payment Terms

1. Payment: **T/T, Western Union, MoneyGram, PayPal**; **30% deposits; 70% balance** before delivery,
2. MOQ: **1pcs**,
3. Warranty: 5 years